

AMERILUBE Series 8

FULL SYNTHETIC COMPRESSOR FLUID

This series of ultra duty compressor lubricants is formulated from Polyol Ester base stock and a synergistic blend of additives designed to provide excellent performance in rotary screw compressors operating at high temperatures. This product is designed for 12,000 hour service at 220°F operation.

Application: Rotary Screw and Rotary Vane

Product Life: Exceptional

Product Features & Benefits

Outstanding Oxidation Stability	Reduced Oil Misting
Very High Viscosity Index	Carbon & Varnish Control
High Flash & Auto-Ignition Points	Reduced Maintenance Cost
Very Low Volatility	Reduced Downtime
Extremely High Film Strength	Excellent Materials Compatibility
Excellent Coolant Properties	Reduced Lubricant Consumption
Long Fluid Life Cycle	Excellent Rust & Corrosion Control

Product		A328	A468	A688
ISO Grade		32	46	68
Index		126	129	131
cSt @	100°F / 40°C	32	45.5	67
cSt @	212°F / 100°C	6.0	7.6	10.1
Flash Point	°F / °C	468/242.2	468 / 242.2	468 / 242.2
Pour Point	°F / °C	-39/-45	-49 / -45	-44 / -42.4
Copper Corrosion, 24 Hr		1a	1a	1a
Demulsibility, 30 Min@130°F		Excellent	Excellent	Excellent

The information provided in this technical literature is believed to be accurate; however, we assume no liability and make no warranty or representation that the information is correct or complete. Conditions of use are known only to the user.



ADVANCED TECHNOLOGY LUBRICANTS
from AMERICAN SYNTHOL

American Synthol, Inc. PO Box 1161, Medina, OH 44258
P 678-461-5751 F 678-461-5752
www.americansynthol.com