AMERILUBE®

Eagle Diesel HD

LONG DRAIN 100% SYNTHETIC ENGINE OIL - API SERVICE CK-4

Eagle Diesel HD 15W40 CK-4 is a premium blend of hydro-cracked base oils with selected additives, designed to give excelent performance in all engines using ultra low sulfur diesel fuel (**ULSD**). its also designed for use in low and high sulfur fuels. This engine oil contains an effective additive system which is DPF compatible and keeps the EGR engines highly clean. It can be used for all new and old engines using ULSD fuel and safe for usage with most of the After Treatment Devices (ATD).

Advantages

- Recommended for all engines using DPF after treatment device and ULSD fuel that specify CK-4, CJ-4, CJ-4
- It meets the performance specification of ACEAE9-16.
- It meets the performance specification for various North American OEMs such as Cummins CES 20086, Mack EO-S 4.5, Detroit Diesel DOC 93K222, Ford WSS-M2C171-F1, and Caterpillar-CAT ECF-3, ECF-1-a, ECF-2.
- It also meets the performance specification for various European OEMs such as MB 228.31, Volvo VDS 4.5 VDS-4, VDS-3, Renault RLO-4, MTU Type 2.1, Deutz DQC III-10 La and JASODH-2.

Features

- Meets and exceeds EPA compliant engine requirements (of newer engines.
- · High TBN with low SAPS.
- · DPF & all ATD compatible.
- Backward compatible with all old and new engines using ultra low, low and high sulfur diesel fuels.
- · Improved oxidation and shear stability.

| Product | HD 15W40 |
|-------------------------|-----------|
| Gravity, °API | 31.1 |
| Flash Point, °F / °C | 453 / 234 |
| Pour Point, °F / °C | -44 / -42 |
| Viscosity @ 100° C. cSt | 15.1 |
| Viscosity Index | 145 |
| CCS @ -20 °C. | 5,120 |
| Color, D-1500 | 3.0 |
| Sulfated Ash, WT. % | 1.0 |
| Calcium, WT. % | 0.24 |
| Zinc, WT. % | 0.12 |
| TBN (D 2896) | 10.0 |

The information provided in this technical literature is believed to be accurate; however, we assume no liability and make no warranty or representation that the information is correct or complete. Conditions of use are known only to the user.



ADVANCED TECHNOLOGY LUBRICANTS from AMERICAN SYNTHOL

American Synthol, Inc. PO Box 1161, Medina, OH 44258 P 678-461-5751 F 678-461-5752 www.americansynthol.com