

AMERILUBE® Eagle PCMO

HIGH PERFORMANCE 100% SYNTHETIC - ILSAC GF-5, API SN, SN-RC

Eagle PCMO lubricants are high performance passenger car engine oils designed to meet the latest car manufacturers warranty requirements. Specifically formulated to meet the demands of the small displacement high RPM fuel efficient engines found in today's domestic and foreign automobiles. These oils are a blend of the synthetic premium base oils and special additives which protects against high temperature oxidation, wear, and viscosity breakdown. They are fortified with detergent-dispersants, rust and corrosion inhibitors and friction modifiers to keep engines exceptionally clean and free of sludge, varnish and rust.

Advantages

- Exceeds ILSAC GF-5 and API SN and SN-RC requirements. Recommended for domestic and foreign high performance engines. Recommended for small, high RPM engines (turbo-charged).
- Meets the warranty requirements of Chrysler (MS 6395S), Ford specification (WSS-M2C946A) and General Motors specification (GMW-16181).

Features

- Meets and exceeds OEMs warranty requirements.
- Protects engine from oil thickening, high temperature sludge and varnish deposits.
- Protects against viscosity breakdown in severe service.
- Keeps engine parts clean.
- Improved fuel economy.
- Protects critical turbo charger bearings and other vital engine surfaces.
- Protects cam lobes and other highly loaded parts from wear.

Test, SAE	ASTM	5W20	5W30	10W30
Gravity, °API	D-287	32.5	31.4	30.3
Flash Point, °F / °C	D-92	444 / 229	419 / 215	428 / 220
Pour Point, °F / °C	D-97	-38 / -39	-33 / -36	-22 / -30
Viscosity @ 100°C, cSt	D-445	8.75	10.9	10.6
Viscosity @ -25°C. CCS	D5293	5,100	5,300	4,500
Viscosity Index	D-2270	155	165	150
Appearance	Visual	Bright & Clear	Bright & Clear	Bright & Clear
Color	D-1500	3.1	3.3	3.2
Zinc, Wt.%		0.085	0.085	0.085
Phos, Wt%		0.077	0.077	0.077
TBN	D-2896	7.9	7.9	7.9

The information provided in this technical literature is believed to be accurate; however, we assume no liability and make no warranty or representation that the information is correct or complete. Conditions of use are known only to the user.



ADVANCED TECHNOLOGY LUBRICANTS
from AMERICAN SYNTHOL

American Synthol, Inc. PO Box 1161, Medina, OH 44258
P 678-461-5751 F 678-461-5752
www.americansynthol.com