

# AMERILUBE® Series SS

## SEMI SYNTHETIC COMPRESSOR FLUID

**Series SS** lubricants are petroleum base fluids with a synergistic blend of additives designed to provide good performance in air compressor applications. Service life of 4,000 hours can be expected under normal operating conditions. **American Synthol's new formulation provides better viscosity stability over a wide range of temperatures.**

**Application:** Rotary Screw

**Product Life:** Good (up to 4,000 hours under normal operating conditions)

### Product Features & Benefits

Outstanding Oxidation Stability	Energy Savings
High Viscosity Index	Carbon & Varnish Control
High Flash & Auto-Ignition Points	Reduced Maintenance Cost
Low Volatility	Reduced Downtime
Extremely High Film Strength	Excellent Materials Compatibility
Excellent Coolant Properties	Reduced Lubricant Consumption
Long Fluid Life Cycle	Excellent Rust & Corrosion Control

Product		A4000C
ISO Grade		32
Viscosity Index		164
cSt @	100°F / 40°C	33.5
cSt @	212°F / 100°C	6
Flash Point	°F / °C	464 / 240
Pour Point	°F / °C	-49 / -45
Copper Corrosion, 24 Hr		1a
Demulsibility, 30 Min@130°F		40/40/0

The information provided in this technical literature is believed to be accurate; however, we assume no liability and make no warranty or representation that the information is correct or complete. Conditions of use are known only to the user.



**ADVANCED TECHNOLOGY LUBRICANTS**  
from AMERICAN SYNTHOL

American Synthol, Inc. PO Box 1161, Medina, OH 44258  
P 678-461-5751 F 678-461-5752  
www.americansynthol.com