



AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

ADI-32

**SUPER PREMIUM SYNTHETIC
FOOD GRADE DRIP OIL**



American Synthol, Inc.

4343 Shallowford Road, Suite D2,
Marietta, GA 30062
Phone: 888-378-9290
Fax: 888-731-9534

AMERILUBE - DRIP OIL

Amerilube ADI-32 Food Grade Drip Oil is a high performance fluid. It fully complies with the requirements of FDA 21 CFR 178.3570 (lubricants with incidental food contact).

Amerilube ADI-32 Food Grade Drip Oil is registered with NSF.

Amerilube ADI-32 Food Grade Drip Oil is specifically formulated for vertical turbine pump bearing, and provide excellent service and are designed for extended drain intervals.

- Excellent Oxidation Stability
- High Viscosity Index
- High Flash & Auto Ignition Points
- Very Low Volatility
- Extremely High Film Strength
- Excellent Coolant Properties
- Very Long Fluid Life
- Energy Savings
- Carbon and Varnish Control
- Reduced Maintenance Costs
- Reduced Downtime
- Excellent Materials Compatibility
- Reduced Lubricant Consumption
- Excellent Rust & Corrosion Control

Typical Properties

Lubricant Designation	ADI-32
Viscosity Index	109
Vis cSt @ 40 °C	32.5
Vis cSt @ 100 °C	4.5
Vis SUS @ 100 °F	152.7
Vis SUS @ 212 °F	40.8
Flash Point °F	438
Auto-Ignition Point °F	731
Pour Point °F	-12
Four Ball, 40 Kg, 1200 RPM, 167 °F	
1 Hr, Scar Dia mm	.45
Four Ball Weld point, Kg	100
Copper Corrosion, 24 Hr.	1a
Demulsibility, 130 °F, 30 min	40/40/0