



AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

ATP-LT

**SUPER PREMIUM SYNTHETIC AIR
TOOL PROTECTOR**

American Synthol, Inc.

4343 Shallowford Road, Suite D2,
Marietta, GA 30062
Phone: 888-378-9290
Fax: 888-731-9534

AMERILUBE ATP-LT

AMERILUBE ATP-LT - Low Temp Air Tool Protector is a super premium, synthetic air tool lubricant. It is made from advance technology synthetic base and blended with the finest additives to provide maximum lubrication, cleaning, and protection for modern air tools.

AMERILUBE ATP-LT - Low Temp Air Tool Protector is specially formulated to work at very low temperatures. It removes deposits, cleans stuck air tools, and provides outstanding service in even the most severe operating conditions.

- Outstanding Oxidation Stability
- Unsurpassed Water Separation
- Very Good Resistance to Freezing
- High Flash & Auto-Ignition Points
- Very High Film Strength
- Excellent Coolant Properties
- Excellent Cleaning Properties
- Superior Penetrating Ability
- Excellent Rust Control
- Carbon and Varnish Control
- Energy Savings
- Reduced Maintenance Costs
- Reduced Lubricant Consumption
- Excellent Lubricating Ability at Very Low Temperatures

Typical Properties

Lubricant Designation	ATP-LT
Viscosity Index	127
Viscosity cSt @ 40 °C	22
Viscosity cSt @ 100 °C	4.6
Viscosity SUS @ 100 °F	106.3
Viscosity SUS @ 212 °F	41.4
Flash Point °F	315
Auto-Ignition Point °F	655
Pour Point °F	-50
Oxidation Stability	4000
Color	<.5
Copper Corrosion, 24 Hr	1a
Rust Test	No Rust
Demulsibility, 130 °F, 30 min	40/40/0