



# AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

## AMERITEMP DE

SUPER PREMIUM SYNTHETIC  
HEAT TRANSFER FLUID

American Synthol, Inc.

4343 Shallowford Road, Suite D2,  
Marietta, GA 30062  
Phone: 888-378-9290  
Fax: 888-731-9534

## AMERITEMP - HEAT TRANSFER FLUID "DE"

AMERITEMP DE HEAT TRANSFER FLUID is made with the finest thermally and oxidatively stable synthetic base fluids. It is further enhanced with proprietary additives that are designed to dissolve carbon and varnish. It is designed to operate at longer and higher temperatures than other synthetic fluids. AMERITEMP DE HEAT TRANSFER FLUID is NON-TOXIC and NON-HAZARDOUS and does not form carbon in most applications.

### Typical Properties

Lubricant Designation	TEST METHOD	
Grade		34
Density @60 °F	D1298	0.89
Color	D1500	0.5
Flash Point °F	D92	440
Fire Point °F	D92	475
Autoignition Temp, °F	E659	693
Viscosity cSt @ 100 °F	D445	35
Viscosity cSt @ 200 °F	D445	5.2
Viscosity cSt @ 600 °F	D445	0.6
Sulphur Content, % mass	X-RAY	<0.01
Carbon Residue, % mass	D189A	0.005
Cu Strip Corrosion	D130	1a
Vapor Pressure, psi @100 °F	D2879	0.094
Vapor Pressure, psi @500 °F	D2879	0.53
Vapor Pressure, psi @600 °F	D2879	2.15