



AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

EAGLE G4™

**SUPER PREMIUM SYNTHETIC
ENGINE LUBRICANT**

American Synthol, Inc.

2930 Mountain Trace

Roswell, GA 30075

Phone: 888-239-3946 / 770-552-6661

Fax: 800-909-9269 / 770-640-1272

www.amerilube.com

AMERILUBE EAGLE G4™

AMERILUBE EAGLE G4™ marine engine oil is a fully synthetic super premium, high performance oil developed specifically for medium and high speed marine diesel engines. EG4™ is the result of American Synthol's extensive research, development, testing and production of synthetic engine lubricants since 1983. This oil uses technology not found in any other engine lubricant produced in the world today. It has demonstrated its ability to reduce friction, decrease fuel consumption, provide maximum protection against wear, reduce lubricant temperatures and provide extra protection against rust and corrosion prevalent in marine environments. AMERILUBE EAGLE G4™ is also available in a 15 TBN version for units operating on higher sulfur content fuels. EAGLE G4™ meets or exceeds the requirements of API CI-4/CI-4 PLUS/SL, GLOBAL DHD-1, ACEA E7/E5/E3/B3/A3, MACK EON PREMIUM PLUS 03, CUMMINS CES 20078/20077/20076/20072/20071, CATERPILLAR ECF-1, DETROIT DIESEL DDC POWER GUARD FORMULA/SERIES200/SERIES4000 CATEGORY 1, MB 228.1/228.3/229.2, MAN 271/3275, MTU-TYPE 2, VOLVO VDS-2/VDS-3, JASO DH-1.

- Outstanding Oxidation Stability
- Outstanding Thermal Stability
- Outstanding Shear Stability
- Outstanding Wear Reduction
- Extended Lubricant Life
- Significantly Improved Rust Protection
- Outstanding Deposit Control
- Friction Reduction
- Very Low Volatility
- Improved Fuel Economy
- Reduced Oil Consumption

Typical Properties

Lubricant Designation	ASTM Test Method	SAE 40	10W50
SAE Viscosity	-	SAE40	10W50
Viscosity Index	D2270	170	171
Vis cSt @ 40 °C	D445	88.9	113
Vis cSt @ 100 °C	D445	14.5	17.5
Pour Point °C	D97	-35	-28
Flash Point °C	D92	227	235
TBN	D2896	12	12
Sulfated Ash, %WT	D874	1.35	1.35