



AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

PSL

**SUPER PREMIUM SYNTHETIC
PENETRATING SPRAY LUBRICANT**

American Synthol, Inc.

4343 Shallowford Road, Suite D2,
Marietta, GA 30062
Phone: 888-378-9290
Fax: 888-731-9534

AMERILUBE PSL

AMERILUBE PSL - Penetrating Spray Lubricant is a super premium, synthetic, light viscosity, general purpose lubricant. It is made from advance technology synthetic base materials and blended with the finest additives to free stuck parts, clean, and provide long lasting, non-gumming lubrication and rust and corrosion prevention.

AMERILUBE PSL - Penetrating Spray Lubricant removes surface rust and other deposits. It lubricates then stays in place to help protect metal parts from rust and corrosion.

- Outstanding Stability
- Unsurpassed Water Separation
- High Flash & Auto-Ignition Points
- Low Volatility
- Very High Film Strength
- Superior Penetrating Ability
- Excellent Rust Control
- Removes Surface Rust & Other Deposits
- Excellent Cleaning Properties

Typical Properties

Lubricant Designation	PSL
Viscosity Index	121
Viscosity cSt @ 40 °C	8.1
Viscosity cSt @ 100 °C	2.39
Viscosity SUS @ 100 °F	53.0
Viscosity SUS @ 212 °F	33.9
Flash Point °F	299
Auto-Ignition Point °F	638
Pour Point °F	-25
Oxidation Stability	3500
Color	Clear
Copper Corrosion, 24 Hr	1a
Rust Test	No Rust
Demulsibility, 130 °F, 30 min	40/40/0