



AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

SGLX-BBA

SUPER PREMIUM SYNTHETIC GEAR
FLUID

American Synthol, Inc.

4343 Shallowford Road, Suite D2,
Marietta, GA 30062
Phone: 888-378-9290
Fax: 888-731-9534

AMERILUBE SERIES SGLX-BBA

AMERILUBE SYNTHETIC GEAR AND BEARING LUBRICANT

AMERILUBE SYNTHETIC GEAR & BEARING LUBRICANTS BBA are premium, Synthetic Products using an advanced technology additive system and special synthetic friction modified base fluids.

AMERILUBE SYNTHETIC GEAR & BEARING LUBRICANTS BBA give outstanding service in even the most demanding applications.

- Excellent Oxidation Stability
- Very High Viscosity Index
- High Flash & Auto-Ignition Points
- Very Low Volatility
- Excellent Film Strength
- Excellent Coolant Properties
- Good Dispersant Properties
- Very Long Fluid Life
- Excellent Rust Control
- Excellent Sludge and Varnish Control
- Reduced Maintenance Costs
- Reduced Downtime
- Reduced Lubricant Consumption
- Excellent Water Separation

Typical Properties

Lubricant Designation	SGLX-BBA100	SGLX-BBA220
Viscosity Index	105	113
Viscosity cSt @ 40 °C	100.1	213.0
Viscosity cSt @ 100 °C	12.0	20.6
Flash Point °F	409	428
Auto-Ignition Point °F	663	676
Pour Point °F	-43	-40
Timken "OK" Load Kg	40	40
Copper Corrosion, 24 Hr	1a	1a
Demulsibility, 130 °F, 30 min	40/40/0	40/40/0