



AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

SHTCL

**SUPER PREMIUM SYNTHETIC
HIGH TEMP CHAIN LUBE**

American Synthol, Inc.

4343 Shallowford Road, Suite D2,
Marietta, GA 30062
Phone: 888-378-9290
Fax: 888-731-9534

SUPER HIGH TEMP CHAIN LUBRICANT

AMERILUBE SHTCL - SUPER HIGH TEMP CHAIN LUBE is a super premium, synthetic lubricant specifically designed to lubricate chains under very severe high temperature service.

AMERILUBE SHTCL is particularly well suited to applications where temperatures exceed 400°F.

AMERILUBE - SHTCL provides outstanding service, even in the most severe operating conditions.

- Outstanding Oxidation Stability
 - Very High Viscosity Index
 - Very High Flash & Auto-Ignition Points
 - Very Low Volatility
 - Extremely High Film Strength
 - Excellent Carbon Control
 - Excellent Materials Compatibility
- Very Tenacious and Long Lasting
 - Excellent Rust Control
 - Excellent Lubricity
 - Energy Savings
 - Reduced Maintenance Costs
 - Reduced Downtime
 - Reduced Lubricant Consumption

Typical Properties

| LUBRICANT DESIGNATION | SHTCL 68 | SHTCL 100 | SHTCL 320 |
|--|----------|-----------|-----------|
| VISCOSITY INDEX | 113 | 109 | 146 |
| Vis cSt @ 40 °C | 64 | 96 | 321.5 |
| Vis cSt @ 100 °C | 8.86 | 11.6 | 33.3 |
| Vis SUS @ 100 °F | - | - | - |
| Vis SUS @ 212 °F | - | - | - |
| Flash Point °F | 468 | 470 | 530 |
| Auto-Ignition Point °F | 756 | 760 | 828 |
| Pour Point °F | -22 | -18 | -24 |
| Four Ball, 40 Kg, 1200 RPM, 167 °F 1Hr, SCAR DIA mm | .40 | .40 | .40 |
| Four Ball Weld Point, Kg | 100 | 100 | 100 |
| Copper Corrosion, 24 Hr | 1a | 1a | 1a |
| Demulsibility, 130 °F, 30 min | 40/38/2 | 40/38/2 | 40/38/2 |