



AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

SERIES SGL-PG

SUPER PREMIUM SYNTHETIC
POLYGLYCOL GEAR LUBRICANT

American Synthol, Inc.

4343 Shallowford Road, Suite D2,
Marietta, GA 30062
Phone: 888-378-9290
Fax: 888-731-9534

AMERILUBE SYNTHETIC POLYGLYCOL GEAR LUBRICANT

AMERILUBE SYNTHETIC POLYGLYCOL GEAR LUBRICANTS are premium, Synthetic Products using an advanced technology additive system and special synthetic friction modified polyglycol base fluids. AMERILUBE SYNTHETIC POLYGLYCOL GEAR LUBRICANTS give outstanding service in even the most demanding applications.

- Excellent Oxidation Stability
- Extremely High Viscosity Index
- High Flash & Auto-Ignition Points
- Very Low Volatility
- Excellent Film Strength
- Excellent Coolant Properties
- Good Dispersant Properties
- Very Long Fluid Life
- Superior Rust Control
- Excellent Sludge and Varnish Control
- Reduced Maintenance Costs
- Reduced Downtime
- Reduced Lubricant Consumption
- Excellent Water Compatibility

Typical Properties

Lubricant Designation	SGL-PG100	SGL-PG150	SGL-PG220	SGL-PG320	SGL-PG460
Viscosity Index	201	207	215	219	244
Viscosity cSt @ 40 °C	92.1	145.2	221.0	318.0	460.2
Viscosity cSt @ 100 °C	17.2	25.0	38.1	49.5	75.1
Viscosity SUS @ 100 °F	-	-	-	-	-
Viscosity SUS @ 212 °F	-	-	-	-	-
Flash Point °F	455	459	448	453	455
Auto-Ignition Point °F	715	721	720	725	726
Pour Point °F	-42	-42	-36	-33	-23
FZG Pass Stage	12+	12+	12+	12+	12+
Copper Corrosion, 24 Hr	1b	1b	1b	1b	1b