



# AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

## SGLX-LT

SUPER PREMIUM SYNTHETIC  
GEAR FLUID

American Synthol, Inc.

2930 Mountain Trace  
Roswell, GA 30075  
Phone: 800-633-5457  
Fax: 888-731-9534

## AMERILUBE SGLX-LT

### LOW TEMPERATURE SYNTHETIC GEAR LUBRICANT

AMERILUBE SYNTHETIC GEAR LUBRICANTS are premium, synthetic products using an advanced technology additive system and special synthetic friction modified base fluids. Proven in countless millions of horsepower hours of service in almost every type of gear application, SGLX-LT is specially formulated to perform in low temperature applications.

AMERILUBE SYNTHETIC GEAR LUBRICANTS give outstanding service in even the most demanding applications.

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>● Excellent Oxidation Stability</li> <li>● High Viscosity Index</li> <li>● High Flash &amp; Auto Ignition Points</li> <li>● Very Low Volatility</li> <li>● Excellent Film Strength</li> <li>● Excellent Coolant Properties</li> <li>● Good Dispersant Properties</li> </ul> | <ul style="list-style-type: none"> <li>● Very Long Fluid Life</li> <li>● Excellent Rust Control</li> <li>● Excellent Sludge and Varnish Control</li> <li>● Reduced Maintenance Costs</li> <li>● Superb Low Temperature Properties</li> <li>● Reduced Lubricant Consumption</li> <li>● Excellent Water Separation</li> </ul> |
|--|---|

### Typical Properties

Lubricant Designation	SGLX-22LT	SGLX-32LT	SGLX-68LT
Viscosity Index	118	125	125
Vis cSt @ 40 °C	23.1	32.0	55.0
Vis cSt @ 100 °C	4.6	5.7	8.4
Vis SUS @ 100 °F	111.1	150.5	256.0
Vis SUS @ 212 °F	41.4	44.9	53.7
Flash Point °F	418	440	440
Auto-Ignition Point °F	667	720	720
Pour Point °F	-59	-55	-55
Timken "OK" Load Lb.	40	40	40
Copper Corrosion, 24 Hr.	1a	1a	1a
Demulsibility, 130 °F, 30 min	40/40/0	40/40/0	40/40/0