



AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS



American Synthol, Inc.

4343 Shallowford Road, Suite D2,
Marietta, GA 30062
Phone: 888-378-9290
Fax: 888-731-9534

AMERILUBE SYNWAY

AMERILUBE SYNWAY - SYNTHETIC WAY LUBRICANTS are super premium, synthetic products using an advanced technology additive system and special synthetic base fluids which provide superior performance in all types of sliding applications.

AMERILUBE SYNWAY - SYNTHETIC WAY LUBRICANTS eliminate "Stick Slip" and chatter on all sliding applications. SYNWAY also has special additives which reduce mixing with soluble oils and protect Ferrous and Nonferrous metals from rust and corrosion.

AMERILUBE SYNWAY lubricants meet Cincinnati Milacron standards P-47 & P-50.

- Unsurpassed Elimination of Chatter
- Very High Viscosity Index
- High Flash & Auto-Ignition Points
- Excellent Shock Loading Performance
- Excellent Film Strength
- Excellent Oxidation Stability
- Good Dispersant Properties
- Very Long Fluid Life
- Excellent Rust & Corrosion Control
- Excellent Sludge and Varnish Control
- Reduced Maintenance Costs
- Reduced Downtime
- Reduced Lubricant Consumption
- Excellent Water Separation

Typical Properties

Lubricant Designation	SYNWAY-68	SYNWAY-220
Viscosity Index	120	121
Vis cSt @ 40 °C	67.1	215.0
Vis cSt @ 100 °C	9.4	21.7
Vis SUS @ 100 °F	-	-
Vis SUS @ 212 °F	-	-
Flash Point °F	465	518
Auto-Ignition Point °F	756	810
Pour Point °F	-22	10
Weld Point, Kg	40	40
Copper Corrosion, 24 Hr.	1a	1a
Demulsibility, 130 °F, 30 min	40/40/0	40/40/0