



# AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

## SERIES SMCL

SUPER PREMIUM SYNTHETIC SAW  
MILL CHAIN LUBRICANT

American Synthol, Inc.

2930 Mountain Trace  
Roswell, GA 30075  
Phone: 800-633-5457  
Fax: 888-731-9534

## SAW MILL CHAIN LUBE

AMERILUBE - SAW MILL CHAIN LUBE is a super premium, synthetic fluid with an advanced technology additive system. It is blended specifically to clean and lubricate saw mill chains. It is particularly effective in removing resins which accumulate over time.

AMERILUBE - SAW MILL CHAIN LUBE sets up a barrier to help prevent accumulation of resins and reduce application time. Its superior anti-wear technology helps to prevent wear and extends chain life.

AMERILUBE - SAW MILL CHAIN LUBE gives outstanding service, even in the most severe operating conditions.

- Outstanding Oxidation Stability
- High Viscosity Index
- High Flash & Auto Ignition Points
- Very Low Volatility
- Extremely High Film Strength
- Excellent Coolant Properties
- Good Dispersant Properties
- Excellent Cleaning Properties
- Long Fluid Life
- Excellent Rust Control
- Carbon & Varnish Control
- Energy Savings
- Reduced Maintenance Costs
- Reduced Downtime
- Reduced Lubricant Consumption
- Excellent Chain Barrier Protection

## Typical Properties

Lubricant Designation	SMCL-15	SMCL-30
Viscosity Index	121	102
Viscosity cSt @ 40°C	13	32.0
Viscosity cSt @ 100°C	3.2	5.4
Viscosity SUS @ 100°F	69.45	150.5
Viscosity SUS @ 212°F	36.85	44.0
Flash Point °F	320	440
Auto-Ignition Point °F	610	735
Pour Point °F	-20	-20
Four Ball, 40 Kg, 1200 RPM, 167°F 1 Hr, Scar Dia mm	.48	.48
Four Ball Weld Point, Kg	60	60
Copper Corrosion, 24 Hr	1a	1a
Demulsibility, 130 °F, 30 min	40/40/0	40/40/0