

AMERILUBE® Series 7

FULL SYNTHETIC COMPRESSOR FLUID

Series 7 compressor lubricants are formulated from several synthetic base stocks (PAO, Ester and Group III) and a synergistic blend of additives designed to provide excellent performance in rotary screw compressors. Amerilube® is manufactured in an ISO 9001:2008 certified facility. The Series 7 lubricants offer outstanding performance at a reduced cost versus most PAO and PAO blends. **American Synthol's new formulation provides better viscosity stability over a wide range of temperatures.**

Application: Rotary Screw, Rotary Vane and Reciprocating Compressors.

Product Life: Excellent (up to 8,000 hours under normal operating conditions)

Product Features & Benefits

Outstanding Oxidation Stability	Energy Savings
High Viscosity Index	Carbon & Varnish Control
High Flash & Auto-Ignition Points	Reduced Maintenance Cost
Low Volatility	Reduced Downtime
Extremely High Film Strength	Excellent Materials Compatibility
Excellent Coolant Properties	Reduced Lubricant Consumption
Long Fluid Life Cycle	Excellent Rust & Corrosion Control

Product	A327C	A467C	A687C	A1007C	A1507C
ISO Grade	32	46	68	100	150
Viscosity Index	131	149	139	129	125
cSt @ 100°F / 40°C	32.31	47.22	68.57	99.87	150.70
cSt @ 212°F / 100°C	5.95	8.22	10.41	13.12	17.27
Flash Point °F / °C	410 / 210	420 / 215	448 / 231	448 / 231	460 / 238
Pour Point °F / °C	-38 / -39	-29 / -34	-29 / -34	-27 / -33	-41 / -42
Copper Corrosion, 24 Hr	1a	1a	1a	1a	1a
Demulsibility, 30 Min@130°F	Excellent	Excellent	Excellent	--	--
Demulsibility, 30 Min@180°F	--	--	--	Excellent	Excellent

The information provided in this technical literature is believed to be accurate; however, we assume no liability and make no warranty or representation that the information is correct or complete. Conditions of use are known only to the user.



ADVANCED TECHNOLOGY LUBRICANTS
from AMERICAN SYNTHOL

American Synthol, Inc. PO Box 1161, Medina, OH 44258
P 678-461-5751 F 678-461-5752
www.americansynthol.com