

AMERILUBE® Series 8

FULL SYNTHETIC COMPRESSOR FLUID

This series of ultra-duty compressor lubricants is formulated from polyol ester (POE) base stock and a synergistic blend of additives designed to provide excellent performance in rotary screw compressors operating at high temperatures. **This product is designed for 12,000 hour service at higher operating temperatures up to 220°F.**

Application: Rotary Screw and Rotary Vane

Product Life: Exceptional (up to 12,000 hours under normal operating conditions)

Product Features & Benefits

Outstanding Oxidation Stability	Reduced Oil Misting
High Viscosity Index	Carbon & Varnish Control
High Flash & Auto-Ignition Points	Reduced Maintenance Cost
Low Volatility	Reduced Downtime
Extremely High Film Strength	Excellent Materials Compatibility
Excellent Coolant Properties	Reduced Lubricant Consumption
Long Fluid Life Cycle	Excellent Rust & Corrosion Control

Product		A328	A468	A688
ISO Grade		32	46	68
Viscosity Index		158	148	146
cSt @	100°F / 40°C	31.8	46.0	68.12
cSt @	212°F / 100°C	6.39	8.05	10.69
Flash Point	°F / °C	458 / 236	461 / 238	480/249
Pour Point	°F / °C	-53 / -47	-68 / -56	-72/-58
Copper Corrosion, 24 Hr		1a	1a	1a
Demulsibility, 30 Min@130°F		Excellent	Excellent	Excellent

The information provided in this technical literature is believed to be accurate; however, we assume no liability and make no warranty or representation that the information is correct or complete. Conditions of use are known only to the user.



ADVANCED TECHNOLOGY LUBRICANTS
from AMERICAN SYNTHOL

American Synthol, Inc. PO Box 1161, Medina, OH 44258
P 678-461-5751 F 678-461-5752
www.americansynthol.com