

AMERILUBE® Series DE

FULL SYNTHETIC COMPRESSOR FLUID

Series DE compressor lubricants are formulated from 100% Diester synthetic base stock and a synergistic blend of additives designed to provide outstanding performance in air compressor applications. This product series is compatible with virtually all materials. **New and improved formulation.**

Application: Rotary Screw, Rotary Vane and Reciprocating Compressors.

Product Life: Exceptional (up to 8,000 hours under normal operating conditions)

Product Features & Benefits

Outstanding Oxidation Stability	Energy Savings
High Viscosity Index	Carbon & Varnish Control
High Flash & Auto-Ignition Points	Reduced Maintenance Cost
Low Volatility	Reduced Downtime
Extremely High Film Strength	Excellent Materials Compatibility
Excellent Coolant Properties	Reduced Lubricant Consumption
Long Fluid Life Cycle	Excellent Rust & Corrosion Control

Product	A320C	A460C	A680C	A1000C	A1500C
ISO Grade	32	46	68	100	150
Viscosity Index	75	68	84	90	92
cSt @ 100°F / 40°C	31.91	46.67	65.07	102	151.2
cSt @ 212°F / 100°C	5.04	6.17	7.94	10.9	14.42
Flash Point °F / °C	410/210	418/214	429 / 220	440 / 227	439/226
Pour Point °F / °C	-56/-49	-51/-46	-56 / -49	-53 / -47	-40/-40
Copper Corrosion, 24 Hr	1a	1a	1a	1a	1a
Demulsibility, 30 Min@130°F	Excellent	Excellent	Excellent	Excellent	Excellent

The information provided in this technical literature is believed to be accurate; however, we assume no liability and make no warranty or representation that the information is correct or complete. Conditions of use are known only to the user.



ADVANCED TECHNOLOGY LUBRICANTS
from AMERICAN SYNTHOL

American Synthol, Inc. PO Box 1161, Medina, OH 44258
P 678-461-5751 F 678-461-5752
www.americansynthol.com