

AMERILUBE® Series SBL

SYNTHETIC BLOWER LUBRICANT

This series of blower lubricants is formulated from polyalphaolefins (PAO) synthetic base stock and a synergistic blend of additives designed to provide superior performance in the gears and bearings of rotary lobe blowers. It is designed specifically to provide long fluid life as well as protection from foaming and air entrainment while supplying maximum protection in all types of rotary lobe blowers.

Application: Rotary Lobe Blowers

Product Life: Exceptional

Product Features & Benefits

Outstanding Oxidation Stability	Energy Savings
Superior Thermal and Shear Stability	Excellent Lubricity and Anti-wear Properties
Excellent Rust & Corrosion Control	Low Volatility
High Flash & Auto-Ignition Points	Carbon & Varnish Control
Extremely High Film Strength	Reduced Maintenance Cost & Downtime
Excellent Coolant Properties	Excellent Materials Compatibility
Long Fluid Life Cycle	Reduced Lubricant Consumption

Product		SBL-220
ISO Grade		220
Viscosity Index		171
cSt @	100°F / 40°C	230
cSt @	212°F / 100°C	24.15
Flash Point	°F / °C	504 / 265
Pour Point	°F / °C	-31 / -35
Copper Corrosion, 24 Hr		1b
Demulsibility, 30 Min@130°F		40/40/0

The information provided in this technical literature is believed to be accurate; however, we assume no liability and make no warranty or representation that the information is correct or complete. Conditions of use are known only to the user.



ADVANCED TECHNOLOGY LUBRICANTS
from AMERICAN SYNTHOL

American Synthol, Inc. PO Box 1161, Medina, OH 44258
P 678-461-5751 F 678-461-5752
www.americansynthol.com