

AMERILUBE® Series SS

SEMI SYNTHETIC COMPRESSOR FLUID

Series SS lubricants are petroleum base fluids with a synergistic blend of additives designed to provide good performance in air compressor applications. Service life of 4,000 hours can be expected under normal operating conditions. **American Synthol's new formulation provides better viscosity stability over a wide range of temperatures.**

Application: Rotary Screw

Product Life: Good (up to 4,000 hours under normal operating conditions)

Product Features & Benefits

Outstanding Oxidation Stability	Energy Savings
High Viscosity Index	Carbon & Varnish Control
High Flash & Auto-Ignition Points	Reduced Maintenance Cost
Low Volatility	Reduced Downtime
Extremely High Film Strength	Excellent Materials Compatibility
Excellent Coolant Properties	Reduced Lubricant Consumption
Long Fluid Life Cycle	Excellent Rust & Corrosion Control

Product		A4000C
ISO Grade		32
Viscosity Index		124
cSt @	100°F / 40°C	32.4
cSt @	212°F / 100°C	5.8
Flash Point	°F / °C	420 / 215
Pour Point	°F / °C	-31 / -35
Copper Corrosion, 24 Hr		1b
Demulsibility, 30 Min@130°F		40/40/0

The information provided in this technical literature is believed to be accurate; however, we assume no liability and make no warranty or representation that the information is correct or complete. Conditions of use are known only to the user.



ADVANCED TECHNOLOGY LUBRICANTS
from AMERICAN SYNTHOL

American Synthol, Inc. PO Box 1161, Medina, OH 44258
P 678-461-5751 F 678-461-5752
www.americansynthol.com